

# ADJUSTABLE SWAYBAR END LINK

PN: 2943

Correct swaybar geometry for improved performance and safety on lifted Jeeps



**DESCRIPT.** Marketing 2,000 char. **AAIA** PIES ID C05 (MKT) **Correct swaybar geometry on lifted vehicles and improve suspension performance on- and off-road**

**Maintain proper balance between front and rear swaybars for safer, more predictable on-road driving**

**Tension-free rod ends offer 45 degrees of mounting alignment for reduced wear on related components**

**Variable length design allows you to accurately set swaybar operating angle**

**Special zinc plating applied for corrosion resistance and long lasting protection**

**Extended** 240 char. C05 (EXT) Adjustable Swaybar End Link; Extended length swaybar end link; Set-to-length; Front or rear; Bolt-on; Pair

**Long** 80 char. C05 (DES) Adjustable Swaybar End Link; Set-to-length; Front or rear; Pair

**Short** 20 char. C05 (SHO) Adjustable End Link

**PRODUCT**

**Merchandising Name** — Adjustable Swaybar End Link

**AAIA Brand ID** B20 BKWD (JKS Manufacturing)

**Category** PCDB Suspension

**Part Term. (ID)** B64 Suspension Stabilizer Bar Link Kit (7580)

**Part Number** B15 2943

**Item GTIN / UPC Code** B10 00814897010130

**Quantity** B32 Pair

**Country of Origin** E10 (CTO) USA

**Life Cycle Status** E10 (LIF) Active (2 - Available to Order)

**PRICING**

**Price - MSRP / List** D35 (LST) \$85.00

**Price - MAP** D35 (RMP) \$76.50

**Price - Jobber** D35 (JBR) \$63.75

**Price Sheet Effective** A70 March 1, 2012

**PACKAGE**

**Package Type** B34 Clamshell

**Height (Inches)** H25 15.150

**Width (Inches)** H30 6.150

**Depth (Inches)** H35 2.400

**Weight (Gross LBS)** H45 3.220

**DIGITAL ASSETS**

**Product Photo - HiRes** P80 (P01) [www.jksmfg.com/media/images/pn\\_2943](http://www.jksmfg.com/media/images/pn_2943)

**Product Data Sheet** P80 (SPE) [www.jksmfg.com/support/data\\_pn\\_2943.pdf](http://www.jksmfg.com/support/data_pn_2943.pdf)

**Installation Guide** P80 (INS) [www.jksmfg.com/support/install\\_pn\\_2943.pdf](http://www.jksmfg.com/support/install_pn_2943.pdf)

**Manufacturer Website** P80 (PAG) [www.jksmfg.com](http://www.jksmfg.com)

**VEHICLE**

**Year Start - End** VCDB 2007-2012

**Make** VCDB Jeep

**Model** VCDB Wrangler JK

**Sub-Model** VCDB All (including Rubicon and Unlimited)

**Position** PCDB Front

**Caution** QDB N/A

**Fitment** QDB Requires 0 to 6.0 in. suspension lift; Not compatible with aftermarket swaybars; Front installation on Rubicon models requires drilling; Attaches to swaybar and axle housing

**Informational** QDB Adjustable length

**Installation** QDB Bolt-on installation

For more information, call 1.877.JEEP.JKS or visit us online at [www.jksmfg.com](http://www.jksmfg.com).

This document contains confidential information and is intended for authorized dealers and distributors of JKS products only. Any unauthorized use, disclosure or distribution is prohibited. Pricing and specifications subject to change without notice. Check manufacturer website for the most current information. ©2012 JKS Manufacturing, Inc. All rights reserved.

Product Data Sheet  
Document Overview  
Revised 03/22/2012

OFF-ROAD & PERFORMANCE UPGRADES FOR JEEP® VEHICLES

