

SWITCHBLADE SWAYBAR SYSTEM

PN: 9100

Selectable design allows Jeep owners to control suspension balance and roll stiffness in a way that was never before possible



DESCRIPT. Marketing 2,000 char. **AAIA** PIES ID C05 (MKT) **Instantly select from five unique resistance levels to suit any speed, terrain and vehicle**

Spring loaded indexing heads allow immediate performance adjustments without using any tools

Unique flexible blade arm design and polished indexing heads enhance vehicle appearance and make a striking impression everywhere you go

Self-contained engagement mechanism is protected from mud, dirt and snow for consistent and dependable operation every time

Adjustable end links accommodate ride height variations and enable tuning of swaybar angle

Silent Select technology eliminates mechanical backlash from the engagement mechanism for quiet operation and seamless vehicle integration



Extended 240 char. C05 (EXT) SwitchBlade Swaybar System; Flexible blade type anti-sway bar; Variable rate - five resistance levels; Front; Includes torsion bar and end links; Bolt-on; Kit

Long 80 char. C05 (DES) SwitchBlade Swaybar System; Variable rate - five resistance levels; Front; Kit

Short 20 char. C05 (SHO) SwitchBlade Swaybar

PRODUCT

Merchandising Name — SwitchBlade Swaybar System

AAIA Brand ID B20 BKWD (JKS Manufacturing)

Category PCDB Suspension

Part Term. (ID) B64 Suspension Stabilizer Bar Assembly (7620)

Part Number B15 9100

Item GTIN / UPC Code B10 00814897010963

Quantity B32 Kit

Country of Origin E10 (CTO) USA

Life Cycle Status E10 (LIF) Active (2 - Available to Order)

PRICING

Price - MSRP / List D35 (LST) \$995.00

Price - MAP D35 (RMP) \$895.50

Price - Jobber D35 (JBR) \$746.25

Price Sheet Effective A70 March 1, 2012

PACKAGE

Package Type B34 Box

Height (Inches) H25 5.000

Width (Inches) H30 8.750

Depth (Inches) H35 36.250

Weight (Gross LBS) H45 24.300

DIGITAL ASSETS

Product Photo - HiRes P80 (P01) www.jksmfg.com/media/images/pn_9100

Product Data Sheet P80 (SPE) www.jksmfg.com/support/data_pn_9100.pdf

Installation Guide P80 (INS) www.jksmfg.com/support/install_pn_9100.pdf

Manufacturer Website P80 (PAG) www.jksmfg.com

AAIA ACES DB

VEHICLE

Year Start - End VCDB 1997-2006

Make VCDB Jeep

Model VCDB Wrangler TJ

Sub-Model VCDB All (including Rubicon and Unlimited)

Position PCDB Front

Caution QDB N/A

Fitment QDB Requires 2.0 to 6.0 in. suspension lift; Mounts through tubular front cross member – cross member must be intact and free of damage; End links attach to front axle housing

Informational QDB Selectable roll resistance settings – 5 unique rates; Adjustable end links accommodate ride height variations

Installation QDB It may be necessary to modify or replace front bumper to ensure proper clearance – refer to instructions; Steering stop adjustments may be necessary to prevent interference between tires and blade arms at full steering lock; Bolt-on installation

For more information, call 1.877.JEEP.JKS or visit us online at www.jksmfg.com.

This document contains confidential information and is intended for authorized dealers and distributors of JKS products only. Any unauthorized use, disclosure or distribution is prohibited. Pricing and specifications subject to change without notice. Check manufacturer website for the most current information. ©2012 JKS Manufacturing, Inc. All rights reserved.

Product Data Sheet
[Document Overview](#)
 Revised 03/22/2012